

800AJ

Sollevatori a braccio articolato diesel Serie 800

Caratteristiche

- Il design brevettato da JLG del braccio QuikStick® riduce notevolmente i tempi di ciclo di sollevamento/abbassamento
- Portata migliore nella sua classe per una produttività ottimizzata
- Stazione di lavoro disponibile con accessori opzionali Sky per aiutarvi a effettuare il lavoro

Dettagli tecnici

- Altezza piattaforma elevata – 24,38 m
- Larghezza totale – 2,44 m
- Portata piattaforma – 230 kg



* Certain options or country standards increase weight.

** Ground bearing pressure applies to standard tires.

Specifications may change to meet country standards or with addition of optional equipment.

800AJ Specifications

Dimensions

Platform Size	36 x 96" / 0.91 x 2.44 m
Overall Width	8' / 2.44 m
Tailswing	2' 6" / 76 cm
Stowed Height	9' 10" / 3.0 m
Stowed Length	36' 6" / 11.13 m
Wheelbase	10' / 3.05 m
Ground Clearance	12" / 30 cm
Weight*	34,300 lb / 15,558 kg
Max. Ground Bearing Pressure**	76 psi / 5.3 kg/cm ²

Reach Specifications

Platform Height	80' / 24.38 m
Horizontal Outreach	51' 10" / 15.8 m
Up and Over Height	32' 1" / 9.78 m
Swing	360° Continuous
Platform Capacity-Restricted	n/a
Platform Capacity-Unrestricted	500 lb / 227 kg

Platform Rotator	180° Hydraulic
Jib (Range of Articulation)	130° (+70, -60)

Chassis

Drive Speed 2WD or 4WD	3.0 mph / 4.8 kmph
Gradeability 2WD	30%
Gradeability 4WD	45%
Turning Radius (Inside)	
Turning Radius (Inside) - 2WS	12' / 3.66 m
Turning Radius (Inside) - 4WS	7' / 2.13 m
Turning Radius (Outside)	
Turning Radius (Outside) - 2WS	22' 6" / 6.86 m
Turning Radius (Outside) - 4WS	14' 6" / 4.42 m
Tire Size-2WD	385/65 x 19.5
Tire Type-2WD	Pneumatic Lug Tread
Tire Size-4WD	445/55 x 19.5
Tire Type-4WD	Wide Lug Tread

Power Source

Dual Fuel Engine	GM Vortec 3000 MPFI 82 hp / 61 kW
Diesel Engine	Deutz D2011L04 64 hp / 47kW - Caterpillar 3044C 63.3 hp / 48 kW
Fuel Tank Capacity	39 gal. / 147.63 L
Hydraulic Reservoir	40 gal. / 151.42 L
Auxiliary Power	12V DC
Noise Level	70 dBa @ 7 meters